

EQUIPMENT CO., INC. 5200 COLORADO BLVD. COMMERCE CITY, CO 80022

PHONE: 303-298-7370

FAX: 303-298-8527

DATE 07/10/19 ***QUOTE***

PAGE 1 19-1-1590

www.koisbrothers.com

SOLD TO:

MCCANDLESS INTERNATIONAL

16704 EAST 32ND AVE. AURORA CO 80011

SHIP TO:

TOWN OF ERIE RICH LUCAS 150 BONNELL AVENUE ERIE CO 80516

CUSTOMER PO QUOTE	CUSTOMER NUM 18650	======== SHIP VIA	SALESMAN 2	TER NET		======================================
PART NUMBER	DESCRIPTION		QTY ORD	UOM	PRICE	EXTENDED
SNOWPLOW PACKAG	===== ================================	7507 CHASSIS	1.00	=== EA	150,671.0	== ====== 00 150,671.00
	INCLUDES - Hook L		Snowplow,	Wing	Plow,	,,
96-10-24 STELLA	*SHUTTE HOOKLIFT,	24K CAPACITY	1.00	EA	0.0	0.00

Lifting Capacity:

- 24,000 pounds gross weight

Container Length:

- 10-foot through 12.5-foot from front A-frame to rear of skid rails. Longer bodies up to 14-feet may be accommodated if a full dump angle is not required

Maximum Dump Angle: 54 degrees

Operating Pressure: 4200 PSI maximum.

Weight of Hooklift: 2,600 pounds.

Height of Hooklift Frame:

- Hooklift frame height not to exceed 8.38" as measured from top of truck frame to top of hooklift rollers.

Hook Height:

- 54-inches from bottom of skid rails to bottom of hook bar. Hooklift must be able to pick up body 10-inches below grade, when mounted on a 41 truck frame height.

Tilting Hook Assembly:

- Hooklift must have pivoting type front tilt section (jib) to provide a low degree loading/unloading angle. Hook includes an automatic mechanical safety latch which disengages only when the container/body is in proper position to be picked-up



FAX: 303-298-8527

www.koisbrothers.com

DATE 07/10/19 ***QUOTE***

PAGE 2 19-1-1590

SOLD TO:

MCCANDLESS INTERNATIONAL

16704 EAST 32ND AVE. AURORA CO 80011

SHIP TO:

TOWN OF ERIE RICH LUCAS 150 BONNELL AVENUE ERIE CO 80516

CUSTOMER PO CI	USTOMER NUM	SHIP VIA	SALESMAN	TERMS	CUSTOMER PHONE	
QUOTE 1	8650		2	NET 10	303-926-2893	
PART NUMBER	DESCRIPTION		QTY ORD	UOM PRICE	EXTENDED	
=======================================	= =============	========	======	=== ======	=== ======	

or dropped-off.

Tilt Cylinder:

- Single 4-inch bore with 2-inch diameter rod cylinder. Cylinder must be double acting and include dual integral pilot-operated counterbalance valves to prevent cylinder collapse in case of

Cylinder must be fully retracted when in the transport mode to prevent exposure of cylinder rod to corrosive road salts. Tilt Section Operation:

- Hooklift includes a hydraulic lock-out device to prevent operation of the tilt section while hooklift is in the dumping mode. Lift/Dump Cylinder:
- Single 5.5-inch bore with 2.5-inch diameter rod cylinder. Cylinder must be double acting and include dual integral pilot-operated counterbalance valves to prevent cylinder collapse in case of hose failure.

Dump/Tilt Interlock:

- Dumping is accomplished through a rear pivot. Tilt and lift sections lock into a rigid full length 25 wide frame to provide support for the container while in the dump mode. These sections form this frame without the use of mechanical latches which rely on gravity, not springs, or container/body mounted latches.

The system is protected from out of sequence operation. Tab Alarm:

- Tilt / Dump, Audible alarm to alert operators that they have operated hooklift out of sequence and need to replace 1/4" shear bolt in dump tab.



PHONE: 303-298-7370 FAX: 303-298-8527

www.koisbrothers.com

07/10/19 ***OUOTE***

PAGE 3 19-1-1590

SOLD TO:

MCCANDLESS INTERNATIONAL

16704 EAST 32ND AVE. AURORA CO 80011

SHIP TO:

TOWN OF ERIE RICH LUCAS 150 BONNELL AVENUE ERIE CO 80516

CUSTOMER PO CUSTOMER NUM SHIP VIA SALESMAN TERMS CUSTOMER PHONE 18650 2 NET 10 303-926-2893 PART NUMBER DESCRIPTION QTY ORD UOM PRICE EXTENDED === ======== =======

Rear Body Hold-downs:

- Dual fixed-position hold down devices mounted to the dump frame to secure the body to the hooklift through all ranges of the

This is accomplished without the use of steel springs or hydraulic/air cylinders.

Rear Dump Hinge Pin:

- 2-inch diameter 17-4 stainless steel.

Pins:

- All pins 17-4 stainless steel.

Bushings:

- All bushings to be of the DX pre-lubricated variety Hoses & Hyd. Fittings:
- All hoses and fittings are SAE not metric. O-ring fittings utilized wherever possible

Fenders:

- Poly fenders for use with 22.5 wheels Bumper:
- Heavy duty rectangular tubing bumper with LED light kit compliant with FMVSS108 standards, built in back-up alarm

WHELEN WARNING LIGHT *AND ELECTRICAL SYSTEM INCLUDES

1.00

EA

0.00

0.00

WHELEN DOT LED LIGHTING SYSTEM

CAB SHIELD LIGHTING - DUMP BODY AND SANDER:

- (2) Amber LED lights in recessed steel housing on driver side cab shield (1) front facing and (1) side facing.
- (2) Blue LED lights in recessed steel housing -

EQUIPMENT CO., INC. 5200 COLORADO BLVD. COMMERCE CITY, CO 80022 PHONE: 303-298-7370 FAX: 303-298-8527

WWW.koisbrothers.com

DATE 07/10/19 ***OUOTE*** PAGE 4 19-1-1590

SOLD TO:

MCCANDLESS INTERNATIONAL

16704 EAST 32ND AVE. AURORA CO 80011 SHIP TO:

TOWN OF ERIE RICH LUCAS 150 BONNELL AVENUE ERIE CO 80516

______ CUSTOMER PO CUSTOMER NUM SHIP VIA SALESMAN TERMS CUSTOMER PHONE OUOTE 18650 2 NET 10 303-926-2893 PART NUMBER DESCRIPTION QTY ORD UOM PRICE === ======= _____ on curb side cab shield (1) front facing and (1) side facing. HOOKLIFT LIGHTING: - Steel housing located on rear of hooklift with; - (1) LED amber on driver side and (1) LED blue on curb side. - (2) LED stop / tail / turn and (2) LED back-up light - License plate mount with light, back-up alarm. DUMP BODY - Marker lights SANDER - Work light - LED Smart/Heated ELECTRICAL WIRING: - Centeral wiring and electrical components enclosed in-cab between seats with removable access pannel. - Electrical wiring secured every 18" to top of truck frame with vinyl coated loom clamps. All wire splices or connections utilize Deutsch DT series environmentally sealed connectors. FENDER MOUNTED SNOW *PLOW LIGHTS, LED SMART HEATED 1.00 EA 0.00 0.00 - Mounted on stainless steel tri-pod brackets with heated convex rear view mirrors 10' CARBON STEEL *DUMP BODY - PAINTED ONE BLACK 1.00 EA 0.00 0.00 36" HIGH SIDE, 42" HIGH TAILGATE, 86"I.D. 98" O.D. 7.9 to 9.2 Cubic Yard Capacity FLOOR: 3/16" AR450 steel, one piece no seams FRONT: 56" high, 7 gauge 50,000 psi steel - 36" high, 10 gauge 50,000 psi steel full length outer panel

EQUIPMENT CO., INC. 5200 COLORADO BLVD. COMMERCE CITY, CO 80022 PHONE: 303-298-7370 FAX: 303-298-8527

WWW.koisbrothers.com

DATE 07/10/19 ***QUOTE*** PAGE 5 **19-1-1590**

SOLD TO:

MCCANDLESS INTERNATIONAL

16704 EAST 32ND AVE. AURORA CO 80011 SHIP TO:

TOWN OF ERIE RICH LUCAS 150 BONNELL AVENUE ERIE CO 80516

CUSTOMER PO QUOTE	CUSTOMER NUM SHIP VIA 18650	SALESMAN 2		CUSTOMER PHONE 303-926-2893
PART NUMBER	DESCRIPTION	QTY ORD		EXTENDED
	with one formed horizontal s 6" deep sloping bottom rail, inner panel - for double pan 7 gauge 201 stainless steel 2.25 I.D. side board pockets TAILGATE: - 42" high double panel 10 ga 7 gauge 50,000 psi inner pa with sloped bracing, 1" ste pins with greaseless bushin Electric over air tailgate Single barn door tailgate, and lay flat against body w CAB PROTECTOR: 20" x 84" 10 ga APRON: 8" bolt-on spreader apr LADDERS: (2) Front body mounte (2) Two slide-out lad HOLDERS: (2) Two shovel holder HOOKLIFT FRAME: 54" hook, skid TARP: SHURCO Armatic electric	side brace, 6 7 gauge 50, el sides rear boxed co s, no side box uge 50,000 px nel, Fully box el upper hind gs latch, 3/8" s will swing to fith tie back uge grade 50 on d ladder each ders front un s, (1) winch and 8" x 10"	orner post ards si outer pane oxed perimete ge, 1-1/4" hi spreader chai c curbside & hardware carbon steel h side nderbody each bar holder " rear roller	cail, el er enge ens
DC2500 COUGAR	*12 VOLT VIBRATOR & MOUNT PLAT	E 1.00	EA 0	.00 0.00
	MOUNT CENTER FRONT UNDER DUMP	BODY		
MPJC-6100-3-GEN 5	*ULTRA FORCE AMERICA HYDRAULIC	1.00	EA 0	.00 0.00

SYSTEM INCLUDES:



PHONE: 303-298-7370 FAX: 303-298-8527

www.koisbrothers.com

DATE 07/10/19 ***OUOTE***

PAGE 6 19-1-1590

SOLD TO:

MCCANDLESS INTERNATIONAL

16704 EAST 32ND AVE. AURORA CO 80011

SHIP TO:

TOWN OF ERIE RICH LUCAS 150 BONNELL AVENUE ERIE CO 80516

CUSTOMER PO CUSTOMER NUM SHIP VIA SALESMAN TERMS CUSTOMER PHONE 18650 2 NET 10 303-926-2893 ______ PART NUMBER DESCRIPTION QTY ORD UOM PRICE === ======= =======

- VT35 Tank valve combination with poly cover
- ADD-A-FOLD control valve, temp and level sensor,
- FASD45L front engine crank shaft driven piston pump, pump shut off valve, 2" suction line ball valve. CONTOLS:
- Ultra seat mounted 3-stick controls -Dual axis plow, Single axis hoist, Single axis Jib
- Valves

Double acting hook hoist - high pressure Double acting jib - high pressure Double acting plow lift with integrated float Double acting plow angle 0-14 GPM Direct liquid or 0-5 pre-wet

0-14 GPM Auger, 0-7 GPM Spinner

PLUMBING:

- Stainless steel hydraulic lines under dump body with rubber hoses to valve, dump body, rear to sander, forward to pump and snowplow
- COUPLING:
- 4 Station Stucchi for snowplow with park station
- 6 Station Stucchi for sander & liquid with park station

HENKE ROAD WARRIOR

- *ECT, PLPM 42"HIGH 12' LENGTH
- 1.00 EA
- 0.00

0.00

- 42" High 12' Length
- Top angle: 3-1/2" x 2-1/2" x .375
- Bottom angle: 4" x 4" x 3/4"
- Ribs: 1/2" with two horizontal braces for added rigidity



DATE 07/10/19 ***OUOTE***

PAGE 7 19-1-1590

SOLD TO:

MCCANDLESS INTERNATIONAL

16704 EAST 32ND AVE. AURORA CO 80011

SHIP TO:

TOWN OF ERIE RICH LUCAS 150 BONNELL AVENUE ERIE CO 80516

______ CUSTOMER PO CUSTOMER NUM SHIP VIA SALESMAN TERMS CUSTOMER PHONE OUOTE 18650 2 NET 10 303-926-2893 _______ DESCRIPTION PART NUMBER QTY ORD UOM PRICE === ======= =======

- (5) moldboard to push-frame connection points with bushings
- 100% continuous welds, no skip welding
- Heavy duty, tubular steel push frame
 - 5" x 2" top tube
 - 6" x 4" lower tube
 - Welded bosses at all critical connection points
- (ECT) external compression trip with (3) adjustable layback positions
- Accumulator system to provide smooth mechanical float operation
- Dual A arm lift with central pivot point to achieve parallel lift and oscillation
- Poly wear sheet between swiveling surfaces reduces friction
 - Bushings at all swivel plate connections increase strength and prevent overtightening
- Flat plate hitch plow portion
- Mechanical float allows plow to follow the profile of the road and float (22.5 inches) over road obstacles without a hydraulic float system.-Mechanical float can quickly react to changes in elevation with less resistance than hydraulic systems.
- Plow floats mechanically, independently of the truck hydraulic
- Low profile backplate while still maintaining 10" of ground clearance
- Rubber Shield
- 1/2" x 8" x 12' SAE 1084 high carbon steel cutting edge
- Parking stands
- Rod Markers



*** CONTINUED NEXT PAGE ***

FAX: 303-298-8527

www.koisbrothers.com

DATE 07/10/19 ***QUOTE***

PAGE 8 19-1-1590

SOLD TO:

MCCANDLESS INTERNATIONAL

16704 EAST 32ND AVE. AURORA CO 80011

SHIP TO:

TOWN OF ERIE RICH LUCAS 150 BONNELL AVENUE ERIE CO 80516

==========	=======================================				
CUSTOMER PO	CUSTOMER NUM SHIP VIA	SALESMAN	TERMS	CUSTOMER PHONE	
QUOTE	18650	2	NET 10	303-926-2893	
=========	=======================================		========	===========	
PART NUMBER	DESCRIPTION	QTY ORD	UOM PRICE	E EXTENDED	
=======================================	==== ==================================	======	=== =====	=========	
	- Paint: Orange, Omaha				
	- Flat plate hitch truck porti				
	- Side plate style truck attac	n kit			
	- Paint: Black				
EV SLECT 10-56	*SWENSON HYDRAULIC DRIVEN V-BO	X 1.00	EA	0.00	
	- 10' Length x 56" High x 82"	Wide hopper	45 dearee sl	one	
	- Constructed of 10 ga 201 sta				
	- Bolt-in 6" wide flange, top (H) beam				
	- 7 ga. Bolt-in replaceable conveyor floor				
- 7 ga. slotted longitudinals for easy gearbox/drive shaft removal					
- Sensored motor					
	- 2" drive shaft, 2" idler shaft, spring loaded chain take-up				
	to the rear of sander				
- Self cleaning pintle style conveyor chain					
(21,000 lbs. tensile strength per strand)					
- 1-1/2" x 3/8" double welded cross bars - Rear chain wiper					
- Drop-N-Loc top screens					
- 12" adjustable height spinner extension					
	- 2 internal baffle, 4 external baffles (3 adjustable, front fixed)				
	- Lower spinner assembly with top mounted motor				
	- Swing-up spinner assembly with rear diverter chute				
	- 20" poly spinner disc				
	- Inverted vee				
	- Rear ladder fold-up				
	- Carbon steel 54" Hook Lift s	id with leg	stands and	rear rollers	

BROTHERS EQUIPMENT CO., INC. 5200 COLORADO BLVD. COMMERCE CITY, CO 80022 PHONE: 303-298-7370 FAX: 303-299 0505

DATE 07/10/19 ***QUOTE***

PAGE 9

SOLD TO:

MCCANDLESS INTERNATIONAL

16704 EAST 32ND AVE. AURORA CO 80011

SHIP TO:

TOWN OF ERIE RICH LUCAS 150 BONNELL AVENUE ERIE CO 80516

	JSTOMER NUM SHIP VIA	SALESMAN 2	TERMS NET 10	CUSTOMER PHONE 303-926-2893
PART NUMBER	DESCRIPTION	QTY ORD	UOM PRIC	E EXTENDED
	LSSH Pre-Wet system bulk fill - (2) 115 gallon tanks	=====	=== ====	========
MISCELLANEOUS PARTS	*AND SHOP SUPPLIES	1.00	EA	0.00 0.00
LABOR INSTALL	INSTALLATION LABOR	1.00	EA	0.00 0.00
PAINT DUMP BODY,	**ASSEMBLE TRUCK AND EQUIPMENT **FRONT BUMPER AND TOUCH-UP	1.00	EA	0.00 0.00

All returned goods must be accompanied by invoice and are subject to handling charge after 30 days.

NO RETURNS AFTER 90 DAYS	Sub Total	150,671.00
A SERVICE CHARGE OF 2% PER MONTH, 24% PER ANNUM WILL BE ADDED TO ANY INVOICE NOT PAID.	Sales Tax	0.00
BY THE LAST DAY OF THE MONTH IN WHICH IT IS DUE. WE ARE CONFORMING WITH THE FAIR LABOR	F.E.T.	0.00
STANDARDS ACT OF 1938 AS AMMENDED NOT RESPONSIBLE FOR TIME LOST DUE TO FIRE, STRIKE	Freight	0.00
OR CAUSES BEYOND OUR CONTROL. STENOGRAPHICAL AND CLERICAL ERRORS SUBJECT TO CORRECTION		
THANK YOU FOR ALLOWING US TO QUOTE THESE ITEMS. YOUR COST IS	TOTAL	150,671,00